

Easy-R



Standard equipment:

Easy-R 50BT

- 5.511.1097
PPL brush Ø 483 mm - 19"



Easy-R 55BT

- 2 x 5.511.1101
PPL brush Ø 275 mm - 10"



Easy-R 66BT

- 2 x 5.511.1105
PPL brush Ø 330 mm - 13"



- 4.508.X468
Front squeegee blade L.830 mm
Shore 40 Th. 2.5 mm
- 4.508.X467
Rear squeegee blade L.870 mm
Shore 40 Th. 3 mm



- Suitable to work for the maintenance and deep cleaning of large areas (up to 2.200 m²)
- User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch
- Large handle with traction driving lever for forward and backward directions
- Self levelling brush plate
- Cover removable without tools provided with self locking system
- Quick vacuum motor and filter inspection, without tools
- Detergent solution tank with large opening protected by quick locking cap
- Parking brake directly on the wheel
- Non-marking wheels
- Easy squeegee regulation without tools
- Movable shock-proof squeegee
- Hour meter and solenoid valve.

	Easy-R 50BT	Easy-R 55BT	Easy-R 66BT
code	8.516.0406	8.516.0407	8.516.0415
power supply	24V	24V	24V
scrubbing / squeegee width	500 / 800 mm	550 / 800 mm	660 / 800 mm
max working capacity	2250 m ² /h	2475 m ² /h	2970 m ² /h
detergent tank capacity	67 l / 17.70 gal	67 l / 17.70 gal	44 l / 14.52 gal
recovery tank capacity	75-95 l / 20.35-25 gal	75-95 l / 20.35-25 gal	55-65 l / 14.52-17.17 gal
traction	automatic	automatic	automatic
RPM / pressure on the brushes	150/35 kg /77.16 lbs	150/45 kg /99.20 lbs	150/24 kg /52.91 lbs
brush motor power	600 W	600 W	600 W
detergent solution system	solenoid valve	solenoid valve	solenoid valve
depression / vacuum motor	1280 mmH ₂ O / 480W	1280 mmH ₂ O / 480W	1280 mmH ₂ O / 480W
dimensions / weight	135x56x102 cm / 97 kg	128x71x106 cm / 100 kg	128x71x106 cm / 109 kg



User friendly control panel. Speed adjustment selectors. General ON/OFF and key switch, brush and vacuum motor switch. Thermal circuit breaker to protect vacuum motor and brush motor, battery level control, hour meter.

Optional accessories:



- 2 x 0.107.0002 Tubular battery Pb-acid 12V 118Ah C5



- 2 x 0.107.0063 GEL Battery 12 MFP 105 12V 105Ah C5



- 0.108.0001 Battery Charger 24V 12A 220-240/50-60



- 5.511.1494 On-board Battery charger kit - 24V - 12A



- 4.508.1178 Polyurethane front blade L.830 TH. 3
- 4.508.1177 Polyurethane rear blade L.870 TH. 4



- 5.511.1098 Tynex brush Ø 483 mm-19"
- 5.511.1102 Tynex brush Ø 275 mm-10"
- 5.511.1106 Tynex brush Ø 330 mm-13"

- 5.511.1128 PPL 0,03 brush Ø 483 mm-19"
- 5.511.1254 PPL 0,03 brush Ø 275 mm-10"
- 5.511.1255 PPL 0,03 brush Ø 330 mm-13"

- 5.511.1206 PES brush Ø 483 mm - 19"
- 5.511.1201 PES brush Ø 275 mm-10"
- 5.511.1202 PES brush Ø 330 mm-13"



- 5.511.1099 EWU pad driver Ø 483mm-19"
- 5.511.1103 EWU pad driver Ø 275mm-10"
- 5.511.1107 EWU pad driver Ø 330mm-13"



- 6.508.0034 - Ø 483 mm-19"- beige
- 6.508.0041 - Ø 483 mm-19"- green
- 6.508.0048 - Ø 483 mm-19"- black
- 6.508.0095 - Ø 280 mm-11"- beige
- 6.508.0096 - Ø 280 mm-11"- green
- 6.508.0097 - Ø 280 mm-11"- black
- 6.508.0030 - Ø 340 mm-13"- beige
- 6.508.0037 - Ø 340 mm-13"- green
- 6.508.0044 - Ø 340 mm-13"- black

Easy access to battery and vacuum motor compartment, without using tools. Large tank capacity, at the top in the category (67 l). 2 x 12V -118 Ah C5 batteries to grant long work autonomy, up to 3 hours.



Control lever for brush operation and detergent water outflow. Recovery tank drain hose. Quick fitting battery charger plug.

Heavy duty 15 mm steel monobloc brush plate. Great pressure on the floor for a deep cleaning even on the toughest dirt. Self levelling system. Solenoid valve to stop the detergent water outflow during the work interruptions.

