



IMPRESSIONS™

Brilliant Gloss / Ultra Wear Floor Finish

Description

A proprietary blend of synergistic polymers provide uncompromised benefits of immediate wet look gloss and outstanding wearability. Sophisticated integrated components allow for rapid drying, enhanced leveling and superior repairability. This versatile product can be used in many varied environments and maintained with both high & low speed equipment.

Product Features / Benefits

- Very hard wear surface / Extremely scuff resistant
- Enhanced leveling; repairs easily / Usable by any personnel in many applications
- Super brilliant gloss / Maximizes appearance & user appeal
- Fast drying / Allows faster recoating and less waiting
- Pure thermoplastic polymers / Very responsive to multi-speed polishing

Specifications

Type	Pure acrylic polymers	Detergent Resistant	Yes
Solids	21 ± .5%	Multi-Speed Buffing	Yes
pH	8.5 - 9.5	Leveling	Excellent
Coverage	2500 sq. ft./gal	Black Mark Resistant	Superior
Drying Time	20-30 minutes	Scuff Resistance	Superior
Color	White, opaque liquid	Soil Resistance	Superior
Odor	Acrylic	Durability	Excellent
Film Appearance	Clear	Recoatibility	Excellent
Powdering	None	Removability	Excellent
Flash Point	None	Immediate Wet Look Gloss	Outstanding
Slip Resistant	Yes	Shelf Life	1 year in original unopened container.
Freeze thaw stable	Yes (3 Freeze Thaw Cycles)		

Directions for Use

A proprietary blend of synergistic polymers provide uncompromised benefits of immediate wet look gloss and outstanding wearability. Sophisticated integrated components allow for rapid drying, enhanced leveling and superior repairability. This versatile product can be used in many varied environments and maintained with both high & low speed equipment.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be recoated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

Floor Preparation: Strip floor of old finish and wax, paying particular attention to baseboards, corners, under furniture, and built up areas. Rinse thoroughly with clean water and allow to completely dry.

Application: If desired one or two coats of an approved sealer may be used, prior to finish application. Using a clean mop or applicator apply a thin uniform coat of finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24 hour

period. Floor should be thoroughly dry before traffic is allowed in area. **Spray Buff:** To restore original luster, polish with an approved spray buff compound or laminator.

High Speed Burnishing: This is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. The floor should first be damp mopped with a suitable neutral cleaner and allowed to dry. The surface may then, as desired, be dry burnished with a high speed white or tan buffing pad, or using the same equipment, be spray buffed using an approved product. An alternate method, for insuring a long lasting durable surface, would be to apply an approved mop-on restorer or laminator, allow to dry and then to follow the dry buffing procedure. Floor finish can also be polished by auto scrub method.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be recoated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

Safety Information

Meets or exceeds 0.5 coefficient of friction as measured by the James Machine Methodology. ASTM Method D 2047-82

CAUTION: May Be Harmful If Swallowed. Keep out of reach of children. Avoid eye contact. Do not ingest.

For Eyes: Flush with water for 15 minutes. Get medical aid.

If Ingested: Do not induce vomiting. Give water. Get medical aid. Keep from freezing.

Classified by Underwriters Laboratories® for Slip Resistance.

For sale to, use and storage by Service Personnel only.



FLOOR CARE



National Chemical Laboratories
WORLD CLASS CLEANING SOLUTIONS®

401 North 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • FAX (215) 922-5517
www.nclonline.com