

P R O F E S S I O N A L L I N E



DYNAMIC 300e - 380e - 450e





DYNAMIC CLASS A 300e - 380e - 450e

Two motor ultra light carpet cleaner

STRENGTHS

- > Design, technology and construction 100% made in Italy
- > The world's lightest (860g. -1.89 lb on the handle)
- > Low center of gravity provides stability when using the hose
- > Telescopic handle for maximum comfort
- > Ultra strong with metal brush supports with bearings
- > Accessories integrated on board
- > Replacement filter bag on board
- > Integrated dry cleaning system
- > Interchangeable roller covers for carpets and floors
- > High efficiency electric motors (Class A)





DYNAMIC

Reach any area with the maximum manoeuvrability!



THE WORLD LIGHTEST DUAL MOTOR UPRIGHT VACUUM

- Dynamic has a patented weight distribution system that allows to have 860g (1.89lb) of weight on the handle.
- Both motors are positioned on the base housing, all accessories are located on the lower part of the suction body.

MAINTENANCE WITHOUT TOOLS

- > Nothing can be easier.
- > No tools are required to replace the brush roller or to clean the base housing.
- The 5000 RPM brush roller is dynamically balanced. The brush supports are metal with ball-bearings.

ON BOARD TOOLS

The accessories: extension hose 1-4 with handle, telescopic wand, crevice tool, upholstery tool, replacement bag are all positioned on the back of the machine.

PATENTED DRY CLEANING SYSTEM

- In 10 seconds and without any tools you can install the Patented DCS converter and the machine is ready to dry-clean rugs and carpets. The ecological Lindhaus products are available for the maintenance of any textile surface.
- The mechanical action of the brush at 5000 RPM together with the Lindhaus cleaning solutions provide deep cleaning action which leaves your carpets and rugs soft, clean and sanitized.













Dynamic is equipped with 6 stages of filtration. At the final stage an electrostatic microfilter (3M Filtrete) ensures more than 98% of filtration efficiency at 0.3 micron. You can install the optional filters S-Class Hepa for healthcare environments, which assures 99.97% of filtration efficiency at 0.3 micron. To trap offensive odors use the Lindhaus Carbon Active/Microfilters. All exhaust filters are impregnated with Total antiseptic treatment to avoid the outflow of living micro-organisms.

NET EFFICIENCY FILTRATION 100% 99.97 99.06 99.61 99.86 99.86 99.86 99.86 99.86 99.86 99.86 99.86 99.86 100% 99.86 99.86 99.86 99.86 99.86 100% 99.86 99.86 99.86 100% 99.86 99.86 100% 99















APPLICATIONS

Dynamic is available in three sizes and can operate on any size carpeted surface: Hotel rooms, corridors, ballroom, show rooms, stores, restaurants, cinemas, conference rooms, etc.

ELECTRONIC PROTECTION

The electronic circuit permits you to correctly regulate the height of brush roll; it allows the motor to start softly while keeping it at constant speed. The motor will stop immediately should the brush roll get blocked-this will avoid damage to the cogged belt and all the moving parts.

INTERCHANGEABLE

Thanks to the interchangeable shoe plates Dynamic can be used also on hard floors:

- > with squeegee and front wheels for common hard floors: ceramic, linoleum, etc..
- > with felt for delicate floors: marble and wood





The company Lindhaus srl reserves its right to make any modifications without any prior notice.

TECHNICAL SPECIFICATIONS	Dynamic 300e	380e	450 e
Input power (W)	930	930	950
Vacuum mm/H ₂ O / (inch/H ₂ O)	2300 (79)	2300 (79)	2300 (79)
Air flow (lt/sec)/cfm	49 (102.8)	49 (102.8)	49 (102.8)
Motor protection system	thermal/amp.	thermal/amp.	thermal/amp.
Two ply paper bag lt.	4,5	4,5	4,5
Tnt washable bag	optional	optional	optional
Microfilter 3m filtrete	standard	standard	standard
S-class hepa filter	optional	optional	optional
Cogged drive belt	standard	standard	standard
Overload electronic control	standard	standard	standard
Convergent bristles brush rpm.	5000	5000	4500
Working capacity sqm/h (sqft/h)	480 (5200)	630 (6800)	750 (8000)
Noise level db (A)	68,6	68,6	68,6
Total weight kg (lb)	7,59 (16.73)	7,86 (17.33)	8,16 (17.99)
Handle weight kg (lb)	0,86 (1.89)	0,86 (1.89)	0,86 (1.89)
Cord length mt. (Ft)	10 (41)	10 (41)	10 (41)

APPROVALS:









HEADQUARTERS > LINDHAUS SRL Via Belgio, 22 Z.I. 35127 > Padova, ITALY tel. +39 0498700307 > fax +39 049 8700605 vacuum@lindhaus.it > www.lindhaus.it

Minneapolis > Minnesota USA > ph. 800-498-7526 info@lindhaus.com > www.lindhaus.com



